



REFLECT

WALL PANELS



Reflect Tile (PVC)

Reflect Tile (PVC)

Care Instructions and Guarantee

Reflect Tile panels are guaranteed against faulty materials or manufacture for a period of 10 years when installed and maintained in accordance with Reco Surfaces instructions. Download full instructions for Reflect Tile before fitting.

Reflect Tile and Reco Seal System™

Panel Joins – Invisible joins - Tile panel edges exactly match tile joins in the body of the panel to create a seamless appearance.

Flat seam – No surface profiles. Avoids trapped dirt and germs. Creates the seamless appearance of perfectly installed Tiles.

Double Seal – 'Watertight joins' supported by internal and external corners that can be easily and perfectly aligned, without scribing, using Reflect Backing strips if required.

Line Bending – Reflect Tile is ideal for line bending using professional equipment. This avoids corner joints and can assist the optimum use of material.

Easy replacement and recycling – All Reflect panels are designed to be easily replaced and recycled at the end of their life. Correctly installed panels can be removed without damage to the surface behind and a new panel fitted. Installation offcuts can be returned to Reco Surfaces Ltd, Enterprise House, Freiston, Boston, Lincs PE22 0JZ.

















100% recyclable – Replaced panels which have been installed in accordance with the Reco Seal System™ can be recycled if returned to Reco.

Key Features & Advantages over Ceramic Tiles

- 20% more insulation
- No strip out. Fit over existing tiles or other sound surface
- 100% recyclable. No landfill
- 100% waterproof
- No waterproof tanking materials required
- No grout. No Mould
- 1/3rd the fitting time
- Virtually maintenance-free
- No skilled labour required
- Low carbon footprint
- Cost savings to installer

Reflect Tile (PVC)

Data Sheet

	Panel Type Reflect Tile PVC	100% PVC
	Panel Size 1200 x 2440 x 3mm	
	Weight 6.78kg	(1.97kg per m ²)
	Finish Gloss	Satin Finish On Request
	Scratch Resistance Teflon Hard Coat	Very Good
	Water Resistance Non porous	100% Waterproof
	Chemical Resistance Teflon Hard Coat	Excellent resistance ^A
	Slip Resistance Gloss finish	Not suitable for floors
	Cleaning Easy Clean / Mould Resistant	No need for abrasive cleaning
	Cutting Jigsaw / Fine-Toothed Saw	Easy to cut
	Fixing HG Adhesive	No profiles. Seamless joints
	Density (ISO 1183) D-792	1.10 g/cm ³
	Impact Strength (ISO 179/fa) CHARPY at 23°C	9 KJ/m ²
	Softening Temp (ISO 306A) VICAT D-1525-B	72°C
	Flame Resistance BS476 Part 7	Class 1 ^B
UV	UV Resistance Anti UV Coating	Good
	Recyclable 100% Recyclable	EPDF2 - Energy Performance ^C

- A Resistant to a wide range of chemicals. Specific details available on request.
- B When adhered to plasterboard or equivalent FR material and fitted per Reco instructions. Suitable for all areas. For Splash-backs allow a minimum of 60mm between the rear edge of the hob. With naked flame gas hobs allow a minimum of 100 mm and fit clear heat resistant glass in front of the panel, the width of the hob.
- C Send back to Reco to be recycled (not suitable for standard disposal).

Reflect Wall Panels are manufactured and supplied by Reco Surfaces Ltd.



Head Office:

Enterprise House
Priory Road, Frieston
Boston, Lincolnshire
PE22 0JZ

+44 (0) 330 058 0198

info@reco-surfaces.com

www.trade.reco-surfaces.com